



上海冰畅制冷设备有限公司

法国美优乐全封闭压缩机型号参数图表

型号	TE	-25		-20		-15		-10		-5		0		5		10		15	
	TC	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.	P.F.	P.A.
MT-28	30	2150	1.18	2950	1.35	3880	1.5	4940	1.62	6150	1.71	7520	1.76	9060	1.76	10790	1.7	12710	1.57
	40	1690	1.22	2450	1.41	3330	1.59	4320	1.75	5460	1.89	6750	1.99	8190	2.05	9810	2.06	11610	2.01
	50					2730	1.65	3660	1.87	4700	2.06	5890	2.23	7220	2.36	8720	2.44	10390	2.48
	60									3880	2.21	4950	2.45	6160	2.66	7510	2.84	9030	2.97
MT-36	30	2190	1.52	3920	1.71	5070	1.89	6390	2.06	7870	2.21	9540	2.33	11410	2.41	13490	2.46	15790	3.97
	40	2280	1.63	3240	1.84	4330	2.05	5580	2.25	6980	2.44	8550	2.61	10310	2.75	12260	2.85	14420	2.43
	50					3560	2.2	4710	2.45	6010	2.64	7470	2.91	9090	3.11	10900	3.29	12910	3.11
	60									4980	2.94	6300	3.22	7780	3.5	9430	3.75	11260	3.8
MT-40	30	3190	1.54	4270	1.8	5500	2.04	6900	2.24	8480	2.41	10250	2.52	12230	2.57	14440	2.54	16880	4.47
	40	2430	1.71	3480	2	4680	2.28	6030	2.54	7570	2.77	9290	2.95	11210	3.07	13340	3.13	1570	3.29
	50					3830	2.47	5140	2.79	6610	3.08	8270	3.34	10110	3.56	12160	3.71	14440	3.87
	60									5630	3.34	7210	3.69	8970	4.01	10930	4.27	13100	4.45
MT-50	30	3650	1.67	4750	1.95	6130	2.23	7820	2.49	9880	2.73	12330	2.94	15240	3.11	18630	3.23	22550	5.02
	40	2910	1.9	3840	2.2	5210	2.51	6770	2.81	8680	3.09	10960	3.34	13660	3.56	16830	3.74	20510	3.81
	50			3140	2.4	4280	2.74	5680	3.08	7400	3.41	9470	3.72	11940	4	14860	4.25	18260	4.75
	60							4560	3.29	6070	3.68	7900	4.06	10110	4.41	12740	4.74	15830	5.68
MT-64	30	4400	2.18	6010	2.56	7940	2.92	10230	3.25	12920	3.52	16050	3.73	19660	3.86	23800	3.89	28510	6.58
	40	3470	2.47	4960	2.89	6740	3.31	8850	3.69	11320	4.04	14200	4.34	17530	4.56	21360	4.7	25710	5.57
	50			4100	3.11	5690	3.59	7570	4.06	9780	4.5	12370	4.9	15370	5.23	18830	5.5	22790	6.37
	60							6460	4.31	8370	4.86	10620	5.37	13250	5.84	16310	6.25	19830	7.32
MT-80	30	5520	2.94	7600	3.34	10050	3.75	12910	4.14	16230	4.51	20030	4.85	24380	5.14	29290	5.39	34820	8.44
	40	4390	3.27	6320	3.71	8580	4.15	11210	4.59	14250	5.01	17740	5.41	21720	5.78	26230	6.1	31320	5.26
	50			5320	4.14	7330	4.63	9670	5.12	12380	5.62	15500	6.09	19060	6.54	23110	6.96	27690	6.44
	60							8380	5.77	10700	6.34	13380	6.9	16480	7.44	20010	7.96	24040	7.76
MT-100	30	7300	3.96	9690	4.39	12580	4.84	16030	5.22	20130	5.5	24930	5.67	30510	5.71	36930	5.57	44250	9.2
	40	5360	4.03	7560	4.58	10210	5.12	13370	5.6	17120	6.1	21520	6.32	26640	6.51	32550	6.56	39320	7.37
	50			5870	4.73	8210	5.37	11010	5.98	14340	6.54	18270	7.02	22870	7.4	28190	7.65	34330	9.03
	60							9100	6.37	11950	7.1	15330	7.77	19330	8.36	24010	8.85	29440	10.74
MT-125	30	9340	4.82	12420	5.4	16140	5.94	20580	6.43	25820	6.85	31940	7.17	39040	7.38	47180	7.45	29440	12.46
	40	7490	5.3	10320	5.95	13710	6.59	17750	7.2	22510	7.75	28090	8.23	34570	8.62	42020	8.89	50530	9.29
	50			8480	6.35	11450	7.11	14990	7.87	19190	8.59	24120	9.26	29880	9.86	36540	10.36	44190	11.37
	60							12400	8.4	15930	9.31	20130	10.2	25070	11.03	30850	11.79	37540	13.52
MT-160	30	11950		15720	6.68	20310	7.53	25820	8.13	32360	8.64	40030	9.04	48960	9.3	59250	9.39	71010	15.68
	40	9660		13120	7.52	17300	8.31	22310	9.06	28250	9.75	35250	10.35	43410	10.84	52840	11.19	63640	11.37
	50			10810	8	14460	8.95	18850	9.88	24090	10.79	30290	11.63	37560	12.38	46000	13.02	55740	13.52
	60							15550	10.54	19960	11.69	25240	12.8	31500	13.86	38840	14.82	473	